

## **AUGER RESULTS EXTENDS GOLD CORRIDOR BY 3KM SOUTH OF THE KOLLO GOLD PROJECT IN BURKINA FASO**

### **HIGHLIGHTS**

- Assay results from regional auger drilling at the Kollo Gold Project in Burkina Faso, West Africa have identified:
  - A potential 3km corridor of gold mineralisation directly south of the Kollo gold project at the Kollo SW target area
  - Gold grades of up to 0.42 g/t in a 2.4km north-easterly trending corridor at the Tangassogo prospect from 800m spaced auger lines
  - Gold mineralisation of up to 0.2 g/t over a 1km corridor to the west of a 16 g/t auger sample<sup>1</sup> at the EBS prospect
  - Auger results are similar in tenor to those at the Kollo South discovery
- Auger geochemical program to be accelerated with three auger rigs working on infill drilling and regional testing

Gold explorer Vital Metals Limited (ASX: VML) is pleased to announce the latest results from an auger drilling program from its 100%-owned Kollo Gold Project in Burkina Faso, West Africa. The permits are located on the highly prospective Markoye Fault Corridor which also hosts West African Resources' high grade 2.2Moz Sanbrado Gold Project.

Commenting on the auger results, Vitals' Managing Director Mr Mark Strizek said:

"The high grades seen in the auger results are a solid vindication of the Company's exploration model. The targets immediately south of the Kollo gold project were inferred from our exploration model as there is no outcrop in the area as it was covered with transported cover at some time. The auger drilling allows us to push through this and effectively sample the bedrock".

"Following the recent capital raising we have substantially expanded the auger drilling campaign which will allow us to test these prospective corridors and deliver a series of drill ready targets."

<sup>1</sup> Result reported previously 27/2/2017 - the Company confirms that it is not aware of any new information or data that materially affects the information included in the previous announcement.

To date, a total of 2,091 auger holes have been drilled for 8,177 metres. A total of 1,400 holes have been sampled and assayed which includes the 421 holes which make up this announcement (Figure 1 and Figure 2) with array results from 691 holes pending.

Auger line spacing at Tangassogo is 800m with 50m spacing along the line. At EBS (Eastern Boundary Shear) spacing between the lines is 500m with 50m spacing along the line. Orientation of auger lines is designed to be perpendicular across interpreted mineralised structures.

A program of infill auger drilling has been planned to test these prospects with additional auger rigs being mobilised to the field. An aggressive program of regional auger drill testing will also continue given the success of the limited program to date.

## ENDS

### Contact:

Mark Strizek  
Managing Director  
Vital Metals Ltd  
Phone: +61 8 9388 7742  
Email: [vital@vitalmetals.com.au](mailto:vital@vitalmetals.com.au)

Media Inquiries:  
Nathan Ryan  
Investor Relations  
NWR Communications  
Telephone: +61 420 582 887  
Email: [nathan.ryan@nwrcommunications.com.au](mailto:nathan.ryan@nwrcommunications.com.au)

### Competent Person's Statement

The information in this report that relates to Exploration Targets, Exploration Results, Mineral Resources or Ore Reserves is based on information compiled by Mr Mark Strizek, a Competent Person who is a Member of The Australasian Institute of Mining and Metallurgy. Mr Strizek is a full time employee of the Company. Mr Strizek has sufficient experience that is relevant to the style of mineralisation and type of deposit under consideration and to the activity being undertaken to qualify as a Competent Person as defined in the 2012 edition of the "Australasian Code for Reporting of Exploration Results, Mineral Resources and Ore Reserves". Mr Strizek consents to the inclusion in the announcement of the matters based on his information in the form and context in which it appears.

### Forward looking statements


Certain written statements contained or incorporated by reference in this new release, including information as to the future financial or operating performance of the Company and its projects, constitute forward-looking statements. All statements, other than statements of historical fact, are forward-looking statements. The words "believe", "expect", "anticipate", "contemplate", "target", "plan", "intend", "continue", "budget", "estimate", "may", "will", "schedule" and similar expressions identify forward-looking statements.

Forward-looking statements include, among other things, statements regarding targets, estimates and assumptions in respect of tungsten, gold or other metal production and prices, operating costs and results, capital expenditures, mineral reserves and mineral resources and anticipated grades and recovery rates. Forward-looking statements are necessarily based upon a number of estimates and assumptions related to future business, economic, market, political, social and other conditions that, while considered reasonable by the Company, are inherently subject to significant uncertainties and contingencies. Many known and unknown factors could cause actual events or results to differ materially from estimated or anticipated events or results reflected in such forward-looking statements.

Such factors include, but are not limited to: competition; mineral prices; ability to meet additional funding requirements; exploration, development and operating risks; uninsurable risks; uncertainties inherent in ore reserve and resource estimates; dependence on third party smelting facilities; factors associated with foreign operations and related regulatory risks; environmental regulation and liability; currency risks; effects of inflation on results of operations; factors relating to title to properties; native title and aboriginal heritage issues; dependence on key personnel; and share price volatility and also include unanticipated and unusual events, many of which are beyond the Company's ability to control or predict.


For further information, please see the Company's most recent annual financial statement, a copy of which can be obtained from the Company on request or at the Company's website: [www.vitalmetals.com.au](http://www.vitalmetals.com.au). The Company disclaims any intent or obligation to update any forward-looking statements, whether as a result of new information, future events or results or otherwise. All forward-looking statements made in this new release are qualified by the foregoing cautionary statements. Investors are cautioned that forward-looking statements are not guarantees of future performance and, accordingly, not to put undue reliance on such statements.

Figure 1: Project Location Plan



For personal use only

Figure 2: Vital Metals Burkina Tenement Portfolio – showing auger results and target areas



For personal use only

## Section 1: Sampling Techniques and Data

Criteria	JORC Code explanation	Commentary
Sampling techniques	<ul style="list-style-type: none"> <li>Nature and quality of sampling (eg cut channels, random chips, or specific specialised industry standard measurement tools appropriate to the minerals under investigation, such as down hole gamma sondes, or handheld XRF instruments, etc). These examples should not be taken as limiting the broad meaning of sampling.</li> <li>Include reference to measures taken to ensure sample representivity and the appropriate calibration of any measurement tools or systems used.</li> <li>Aspects of the determination of mineralisation that are Material to the Public Report.</li> <li>In cases where 'industry standard' work has been done this would be relatively simple (eg 'reverse circulation drilling was used to obtain 1 m samples from which 3 kg was pulverised to produce a 30 g charge for fire assay'). In other cases more explanation may be required, such as where there is coarse gold that has inherent sampling problems. Unusual commodities or mineralisation types (eg submarine nodules) may warrant disclosure of detailed information.</li> </ul>	<ul style="list-style-type: none"> <li>The sampling described in this report refers to samples from power auger drilling. The thickness of the regolith horizons were recorded in the field. Approximately 1-2kg of sample was collected by scoop from the drill spoil piles from the bottom of the hole, which was the interface between the regolith and weathered bedrock.</li> <li>Two samples from each auger hole; one from the weathered bedrock and saprolite were sent to ACTLABS in Ouagadougou for BLEG analysis, using cyanide extraction of a 2kg bulk sample with ICP-MS finish, with a detection limit of 1ppb.</li> </ul>
Drilling techniques	<ul style="list-style-type: none"> <li>Drill type (eg core, reverse circulation, open-hole hammer, rotary air blast, auger, Bangka, sonic, etc) and details (eg core diameter, triple or standard tube, depth of diamond tails, face-sampling bit or other type, whether core is oriented and if so, by what method, etc).</li> </ul>	<ul style="list-style-type: none"> <li>All auger holes were drilled using a Mineral Resources Burkina SARL owned and operated Landcruiser mounted power auger fitted with a standard auger blade bit and auger flutes, up which the sample travels to the surface. All auger holes were vertical and targeted weathered bedrock/saprolite.</li> </ul>
Drill sample recovery	<ul style="list-style-type: none"> <li>Method of recording and assessing core and chip sample recoveries and results assessed.</li> <li>Measures taken to maximise sample recovery and ensure representative nature of the samples.</li> <li>Whether a relationship exists between sample recovery and grade and whether sample bias may have occurred due to preferential loss/gain of fine/coarse material.</li> </ul>	<ul style="list-style-type: none"> <li>A technician is always present at the rig to monitor and record recovery and Vital Metals employees managed sampling to ensure correct sampling practices. Samples were visually checked for recovery, moisture and contamination was not observed to be an issue over the mineralised zones. No significant bias is expected and any potential bias is not considered material.</li> </ul>
Logging	<ul style="list-style-type: none"> <li>Whether core and chip samples have been geologically and geotechnically logged to a level of detail to support appropriate Mineral Resource estimation, mining studies and metallurgical studies.</li> <li>Whether logging is qualitative or quantitative in nature. Core (or costean, channel, etc) photography.</li> <li>The total length and percentage of the relevant intersections logged.</li> </ul>	<ul style="list-style-type: none"> <li>All auger drilling has been logged to a high standard however auger drill samples are not used in any future Mineral Resource estimation or mining studies and metallurgical studies.</li> </ul>

<p><i>Sub-sampling techniques and sample preparation</i></p>	<ul style="list-style-type: none"> <li>• <i>If core, whether cut or sawn and whether quarter, half or all core taken.</i></li> <li>• <i>If non-core, whether riffled, tube sampled, rotary split, etc and whether sampled wet or dry.</i></li> <li>• <i>For all sample types, the nature, quality and appropriateness of the sample preparation technique.</i></li> <li>• <i>Quality control procedures adopted for all sub-sampling stages to maximise representivity of samples.</i></li> <li>• <i>Measures taken to ensure that the sampling is representative of the in situ material collected, including for instance results for field duplicate/second-half sampling.</i></li> <li>• <i>Whether sample sizes are appropriate to the grain size of the material being sampled.</i></li> </ul>	<ul style="list-style-type: none"> <li>• <i>The trained drilling and sampling crew limit the sample loss and wall contamination through careful rotation of the auger bit and flutes, resulting in acceptable sample recovery and clear differentiation of lithology horizons.</i></li> </ul>
<p><i>Quality of assay data and laboratory tests</i></p>	<ul style="list-style-type: none"> <li>• <i>The nature, quality and appropriateness of the assaying and laboratory procedures used and whether the technique is considered partial or total.</i></li> <li>• <i>For geophysical tools, spectrometers, handheld XRF instruments, etc, the parameters used in determining the analysis including instrument make and model, reading times, calibrations factors applied and their derivation, etc.</i></li> <li>• <i>Nature of quality control procedures adopted (eg standards, blanks, duplicates, external laboratory checks) and whether acceptable levels of accuracy (ie lack of bias) and precision have been established.</i></li> </ul>	<ul style="list-style-type: none"> <li>• <i>Assaying was completed at ACTLABS laboratories in Ouagadougou by cyanide extraction of a bulk 2kg sample, with low level Au AAS finish, which is considered appropriate for geochemical sampling. This method is appropriate and returns accurate and precise values for gold. Field QAQC procedures included the insertion of field duplicates and commercial standards. The laboratory inserted feldspar flushes, standards, repeats and duplicates. Repeat or duplicate analysis for samples shows that the precision of samples is within acceptable limits.</i></li> </ul>
<p><i>Verification of sampling and assaying</i></p>	<ul style="list-style-type: none"> <li>• <i>The verification of significant intersections by either independent or alternative company personnel.</i></li> <li>• <i>The use of twinned holes.</i></li> <li>• <i>Documentation of primary data, data entry procedures, data verification, data storage (physical and electronic) protocols.</i></li> <li>• <i>Discuss any adjustment to assay data.</i></li> </ul>	<ul style="list-style-type: none"> <li>• <i>Primary data was collected using a set of company standard Excel templates on Toughbook laptop computers using lookup codes. The geo-information was validated on-site by the Company's database technicians and then validated and merged into a final database by the company's database manager. There has not been any adjustment to assay data</i></li> </ul>
<p><i>Location of data points</i></p>	<ul style="list-style-type: none"> <li>• <i>Accuracy and quality of surveys used to locate drill holes (collar and down-hole surveys), trenches, mine workings and other locations used in Mineral Resource estimation.</i></li> <li>• <i>Specification of the grid system used.</i></li> <li>• <i>Quality and adequacy of topographic control.</i></li> </ul>	<ul style="list-style-type: none"> <li>• <i>Auger drill locations as reported have been picked-up using a Garmin GPS. All auger drill holes have been located using UTM grid WGS84 Z30N.</i></li> </ul>
<p><i>Data spacing and distribution</i></p>	<ul style="list-style-type: none"> <li>• <i>Data spacing for reporting of Exploration Results.</i></li> <li>• <i>Whether the data spacing and distribution is sufficient to establish the degree of geological and grade continuity appropriate for the Mineral Resource and Ore</i></li> </ul>	<ul style="list-style-type: none"> <li>• <i>Further auger drilling is required to test zones of gold anomalism.</i></li> <li>• <i>Areas where auger drilling has been conducted are generally spaced on 800m lines and 40m between holes</i></li> </ul>

	<p><i>Reserve estimation procedure(s) and classifications applied.</i></p> <ul style="list-style-type: none"> <li>• <i>Whether sample compositing has been applied.</i></li> </ul>	
<p><i>Orientation of data in relation to geological structure</i></p>	<ul style="list-style-type: none"> <li>• <i>Whether the orientation of sampling achieves unbiased sampling of possible structures and the extent to which this is known, considering the deposit type.</i></li> <li>• <i>If the relationship between the drilling orientation and the orientation of key mineralised structures is considered to have introduced a sampling bias, this should be assessed and reported if material.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Auger drill lines are approximately orientated perpendicular to the orientation of the shear zone.</li> </ul>
<p><i>Sample security</i></p>	<ul style="list-style-type: none"> <li>• <i>The measures taken to ensure sample security.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Chain of custody is managed by Vital. Samples are stored on site and delivered by Vital personnel to ACTLABS Ouagadougou for sample preparation. Whilst in storage, they remain under guard in a locked yard. Tracking sheets are used track the progress of batches of samples</li> </ul>
<p><i>Audits or reviews</i></p>	<ul style="list-style-type: none"> <li>• <i>The results of any audits or reviews of sampling techniques and data.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Vital personnel and consultants have completed numerous site visits and data reviews since acquiring the project. No material issues have been noted.</li> </ul>

## Section 2: Reporting of Exploration Results

Criteria	JORC Code explanation	Commentary
<p><i>Mineral tenement and land tenure status</i></p>	<ul style="list-style-type: none"> <li>• <i>Type, reference name/number, location and ownership including agreements or material issues with third parties such as joint ventures, partnerships, overriding royalties, native title interests, historical sites, wilderness or national park and environmental settings.</i></li> <li>• <i>The security of the tenure held at the time of reporting along with any known impediments to obtaining a licence to operate in the area.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Vital's three contiguous exploration tenements (Doulnia, Kampala and Zeko). The permits are held by Vital Metals Burkina SARL (a wholly owned subsidiary of Vital Metals). The combined area of the permits covers over 400km<sup>2</sup> and give the holder the right to explore for gold. Annual licence fees have been paid up to date with the Burkinabe authorities. The current Mining Code provides free state equity participation of 10 per cent in all companies on the delivery to the company of an industrial exploitation permit for a large-scale mine. This state equity participation is free and non-dilutable. The Doulnia Permit is subject to a 2.25% net smelter royalty with Ampella Mining Burkina SARL. The Mining Code also provides for payment of a gross production royalty ranging from 3% (&lt;US\$1000), 4% (\$1000-1300) and 5% (&gt;\$1300).</li> </ul>
<p><i>Exploration done by other parties</i></p>	<ul style="list-style-type: none"> <li>• <i>Acknowledgment and appraisal of exploration by other parties.</i></li> </ul>	<ul style="list-style-type: none"> <li>• There was a high level of zinc exploration conducted over the area in the mid 1990's to the mid 2000's. A number of drill holes in the immediate vicinity of the Kollo Gold Project were drilled for Zinc by Anmercosa. A number of trenches were completed by Ampella Mining SARL in 2008-</li> </ul>

		2009.
Geology	<ul style="list-style-type: none"> <li>• <i>Deposit type, geological setting and style of mineralisation.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Vital's gold project sits within the Markoye Structural Corridor that is host to several world class gold deposits, including at least two recent major gold discoveries (Cardinal Resources' Namdini Project in Ghana and West African Resources' Tanlouka Project). The geometry of mineralized structures, with significant dilation along steep east-west veins, is consistent with dextral movement along the ENE trending Kollo Shear Corridor. The main rock types observed in diamond core from Kollo are; fine grained moderately to strongly foliated, variably sheared mafic to intermediate intrusive, and; a mixed deformed unit consisting of strongly foliated schist and ductile tectonic breccia. Fe-carbonate, pyrite and strong silica alteration are associated with gold mineralization and hosted in zones of brittle deformation which overprint the sheared intrusive.</li> </ul>
Drill hole Information	<ul style="list-style-type: none"> <li>• <i>A summary of all information material to the understanding of the exploration results including a tabulation of the following information for all Material drill holes:</i> <ul style="list-style-type: none"> <li>○ <i>easting and northing of the drill hole collar</i></li> <li>○ <i>elevation or RL (Reduced Level – elevation above sea level in metres) of the drill hole collar</i></li> <li>○ <i>dip and azimuth of the hole</i></li> <li>○ <i>down hole length and interception depth</i></li> <li>○ <i>hole length.</i></li> </ul> </li> <li>• <i>If the exclusion of this information is justified on the basis that the information is not Material and this exclusion does not detract from the understanding of the report, the Competent Person should clearly explain why this is the case.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Details of individual auger soil geochemistry samples are not tabulated here, as the information required for understanding and interpreting geochemical results of this type is contained in the maps incorporated into or the text of the announcement, or is not considered anomalous or relevant.</li> </ul>
Data aggregation methods	<ul style="list-style-type: none"> <li>• <i>In reporting Exploration Results, weighting averaging techniques, maximum and/or minimum grade truncations (eg cutting of high grades) and cut-off grades are usually Material and should be stated.</i></li> <li>• <i>Where aggregate intercepts incorporate short lengths of high grade results and longer lengths of low grade results, the procedure used for such aggregation should be stated and some typical examples of such aggregations should be shown in detail.</i></li> <li>• <i>The assumptions used for any reporting of metal equivalent values should be clearly stated.</i></li> </ul>	<ul style="list-style-type: none"> <li>• No average weighting or cut offs have been applied to the data in this report.</li> </ul>



<p><i>Relationship between mineralisation widths and intercept lengths</i></p>	<ul style="list-style-type: none"> <li>• <i>These relationships are particularly important in the reporting of Exploration Results.</i></li> <li>• <i>If the geometry of the mineralisation with respect to the drill hole angle is known, its nature should be reported.</i></li> <li>• <i>If it is not known and only the down hole lengths are reported, there should be a clear statement to this effect (eg 'down hole length, true width not known').</i></li> </ul>	<ul style="list-style-type: none"> <li>• Not applicable.</li> </ul>
<p><i>Diagrams</i></p>	<ul style="list-style-type: none"> <li>• <i>Appropriate maps and sections (with scales) and tabulations of intercepts should be included for any significant discovery being reported. These should include, but not be limited to a plan view of drill hole collar locations and appropriate sectional views.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Refer to diagrams in text</li> </ul>
<p><i>Balanced reporting</i></p>	<ul style="list-style-type: none"> <li>• <i>Where comprehensive reporting of all Exploration Results is not practicable, representative reporting of both low and high grades and/or widths should be practiced to avoid misleading reporting of Exploration Results.</i></li> </ul>	<ul style="list-style-type: none"> <li>• The ranges displayed on the maps in this report are considered acceptable for exploration purposes. All relevant exploration data has been included in the maps.</li> </ul>
<p><i>Other substantive exploration data</i></p>	<ul style="list-style-type: none"> <li>• <i>Other exploration data, if meaningful and material, should be reported including (but not limited to): geological observations; geophysical survey results; geochemical survey results; bulk samples – size and method of treatment; metallurgical test results; bulk density, groundwater, geotechnical and rock characteristics; potential deleterious or contaminating substances.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Gold recoveries of &gt;95% Au were obtained from preliminary metallurgical testwork conducted in 2012. These tests confirm that the majority of the gold is free milling and can be recovered using a conventional CIL cyanidation process. The Testwork was conducted on three composite samples created from RC drilling intervals at Kollo South and Kollo Central taken from depths ranging from 70m to 125m. The metallurgical work was undertaken by NAGROM in Australia with confirmatory gold assays undertaken by Ultratrace. No attempt was made in these tests to determine the optimum cyanide dosing rates and this work remains to be completed at a later date. This work has confirmed that the mineralisation is neither preg-robbing nor refractory and provides a solid foundation to any future project studies.</li> </ul>
<p><i>Further work</i></p>	<ul style="list-style-type: none"> <li>• <i>The nature and scale of planned further work (eg tests for lateral extensions or depth extensions or large-scale step-out drilling).</i></li> <li>• <i>Diagrams clearly highlighting the areas of possible extensions, including the main geological interpretations and future drilling areas, provided this information is not commercially sensitive.</i></li> </ul>	<ul style="list-style-type: none"> <li>• Further infill drilling is planned and is ongoing. A figure showing target areas for proposed work programs is included in the body of this report.</li> </ul>

## ABOUT VITAL METALS

Vital Metals Limited (**ASX: VML**) is an explorer and developer , focused on progressing three highly prospective mineral Projects: the Watershed Tungsten Project in far north Queensland, Australia, the Aue Tungsten Project in Saxony, Germany and the Doulnia Gold Project in southern Burkina Faso, West Africa.

### Watershed Tungsten Project – Queensland

The Watershed scheelite (calcium tungstate) Project, in far north Queensland, 150 kilometres north-west of Cairns, is the Company's flagship venture. The Watershed Tungsten Project is a development-ready project that has a completed Definitive Feasibility Study (DFS), is fully permitted and has all landowner and Indigenous agreements in place.

### Aue Tungsten Project – Germany

The Aue Tungsten Project (100% Vital) is located in the western Erzgebirge area of the German state of Saxony. The permit, comprising an area of 78 sq. km is located in the heart of one of Europe's most famous mining regions, being surrounded by several world class mineral fields. Historical mining and intensive exploration work carried out between from the 1940's and 1980's showed high prospectivity of the Aue permit area for tungsten, tin, uranium and silver mineralisation.

### Doulnia Gold Project – Burkina Faso

The Doulnia Gold Project (100% Vital) is located in southern Burkina Faso. The Project is made up of three contiguous permits; the Doulnia, Kampala and Zeko exploration permits. The Project is located in highly prospective Birimian Greenstone terrain with 400 sq. km of contiguous tenements lying on the trend of the Markoye Fault Corridor and hosting the Kollo Gold Project and Boungou South Gold Prospect.

#### Vital Metals Limited

ASX Code: VML

ACN: 112 032 596

Suite 1, 91 Hay Street,  
Subiaco, WA 6008

T: +61 8 9388 7742

F: +61 8 9388 0804

E: [vital@vitalmetals.com.au](mailto:vital@vitalmetals.com.au)

[www.vitalmetals.com.au](http://www.vitalmetals.com.au)

#### Board & Management

David Macoboy  
Chairman

Mark Strizek  
CEO and Managing Director

Peter Cordin  
Non-Executive Director

Andrew Simpson  
Non-Executive Director

Ian Hobson  
Company Secretary

#### Capital Structure

735.7 million shares

91.9 million unlisted options